

## Gigahertz-Solutions HF32D | Meter | YSHIELD® Edition

Basic device. • High frequency (RF): 800 MHz - 2.7 GHz

---



YSHIELD® HF 32D

YSHIELD GmbH & Co. KG  
Rotthofer Straße 1  
94099 Ruhstorf, Germany  
Further information:  
[www.yshield.com](http://www.yshield.com),  
[info@yshield.com](mailto:info@yshield.com)

**YSHIELD® Edition:** We are expanding the scope of delivery of the manufacturer: We enclose a set of brochures of "Diagnose Funk" with information about electrosmog and 5G in GERMAN language. We also add a piece of shielding fabric to simulate high frequency shielding. You can use it to check the effect of shielding on the measurement values.

---

It allows a straight forward assessment of the exposure, a determination of suitable remedial actions, as well as a control of their effectiveness. Simple handling for technical amateurs.

- Measuring range: **1  $\mu\text{W}/\text{m}^2$  up to 1,999  $\mu\text{W}/\text{m}^2$ .**
- Frequency range: **800 MHz up to 2,500 MHz.**
- Accuracy: **6 dB, 9 digit.**
- Field strength proportional audio signal: The higher the measuring value, the faster the acoustic signal.
- Peak value indication.
- Included in delivery: EMR meter device, attachable, direction-finding log.-per. antenna incl. antenna cable, Alkaline Mangan battery, detailed instruction manual (english), factual background information issuing "electric smog".